



HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS



HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS





## HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

- Perfect for LCR applications in high-end home theaters and stereo systems
- Optimum dispersion characteristics both in vertical (left/right channel) and horizontal (center channel) operation
- 3 settings for the tweeter level for an individual sound adjustment
- High-end driver technology with aluminium/ceramic woofer-midrange and coated dome tweeter
- Magnetic front cover in elegant slim design
- Ideal for combination with all Magnat Signature IWT/ICT and Magnat Interior Quantum in-wall/in-ceiling speakers

## 2-WAY HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

### HIGHLIGHTS

- Klippel®-optimized speaker drivers for high efficiency and maximum level
- Large high-end fabric dome with protective diffusor for excellent dynamics and harmonic coupling to the woofer-midrange
- Woofer-midrange with powerful drive system and 3-layer aluminium/ceramic sandwich cone for deep bass reproduction and highest sound precision
- Durable long-throw rubber surrounds for linear operation of the woofer-midrange drivers to handle even large cone excursions
- Woofer-midranges with magnet protection cover to prevent any damage and undesirable background noise
- Elaborate phase-optimized crossover with 3 settings for the tweeter level
- Designed for installation in drywalls (no housing required) or in closed volumes (30 liters or more)
- 6fold clamping mechanism for very easy and robust installation in surfaces of up to 30 mm thickness
- Removable magnetic metal grill with fine perforations and very slim design for an elegant appearance
- Gold-plated push terminals for cables with cross-sections of up to 6 mm<sup>2</sup>





## HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

### PRINCIPLE

2-way in-wall loudspeaker, double woofer

### DRIVERS

2 x 6.5" woofer-midrange  
1 x 1" dome tweeter

### POWER HANDLING (RMS/MAX)

130 / 200 watts

### IMPEDANCE

4 Ω

### FREQUENCY RESPONSE

30 - 28000 Hz

### CROSSOVER FREQUENCIES

2900 Hz

### RECOMMENDED AMPLIFIER OUTPUT

20 - 200 watts

### SENSITIVITY

91 dB

### CABINET SURFACE

White

### DIMENSIONS

Outer dimensions: 220 x 491 mm  
Cutting out: 186 x 456 mm  
Mounting depth: 100 mm

### WEIGHT

3.42 kg

### ART.NO. / EAN

131 2062 / 40 18843 12062 1





### HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

- Perfect for LCR applications in high-end home theaters and stereo systems
- Optimum dispersion characteristics both in vertical (left/right channel) and horizontal (center channel) operation
- 3 settings for the tweeter level for an individual sound adjustment
- High-end driver technology with aluminium/ceramic woofer-midrange and coated dome tweeter
- Magnetic front cover in elegant slim design
- Ideal for combination with all Magnat Signature IWT/ICT and Magnat Interior Quantum in-wall/in-ceiling speakers



## HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

### HIGHLIGHTS

- Klippel®-optimized speaker drivers for high efficiency and maximum level
- Large high-end fabric dome with protective diffusor for excellent dynamics and harmonic coupling to the woofer-midrange
- Woofer-midrange with powerful drive system and 3-layer aluminium/ceramic sandwich cone for deep bass reproduction and highest sound precision
- Durable long-throw rubber surrounds for linear operation of the woofer-midrange driver to handle even large cone excursions
- Woofer-midrange with magnet protection cover to prevent any damage and undesirable background noise
- Elaborate phase-optimized crossover with 3 settings for the tweeter level
- Designed for installation in drywalls (no housing required) or in closed volumes (20 liters or more)
- 6fold clamping mechanism for very easy and robust installation in surfaces of up to 30 mm thickness
- Removable magnetic metal grill with fine perforations and very slim design for an elegant appearance
- Gold-plated push terminals for cables with cross-sections of up to 6 mm<sup>2</sup>



## HIGH-END IN-WALL SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

### PRINCIPLE

2-way in-wall loudspeaker

### DRIVERS

1 x 6.5" woofer-midrange  
1 x 1" dome tweeter

### POWER HANDLING (RMS/MAX)

110 / 180 watts

### IMPEDANCE

4 Ω

### FREQUENCY RESPONSE

32 - 28000 Hz

### CROSSOVER FREQUENCIES

3100 Hz

### RECOMMENDED AMPLIFIER OUTPUT

20 - 180 watts

### SENSITIVITY

91 dB

### CABINET SURFACE

White

### DIMENSIONS

Outer dimensions: 220 x 320 mm  
Cutting out: 186 x 286 mm  
Mounting depth: 102 mm

### WEIGHT

2.15 kg

### ART.NO. /EAN

131 2060 / 40 18843 12060 7







### HIGH-END IN-CEILING SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

- Perfect as surround and high-frequency speaker in high-end home theaters
- Angled speaker unit allows perfect alignment to the listening area
- 3 settings for the tweeter level for an individual sound adjustment
- High-end driver technology with aluminium/ceramic woofer-midrange and coated dome tweeter
- Magnetic front cover in elegant slim design
- Ideal for combination with all Magnat Signature IWT/ICT and Magnat Interior Quantum in-wall/in-ceiling speakers

## HIGH-END IN-CEILING SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

### HIGHLIGHTS

- Klippel®-optimized speaker drivers for high efficiency and maximum level
- Angled speaker unit (15°) allows perfect alignment to the listening area
- Large high-end fabric dome with protective diffusor for excellent dynamics and harmonic coupling to the woofer-midrange
- Tweeter can be pivoted by up to +/-15°
- Woofer-midrange with powerful drive system and 3-layer aluminium/ceramic sandwich cone for deep bass reproduction and highest sound precision
- Durable long-throw rubber surrounds for linear operation of the woofer-midrange driver to handle even large cone excursions
- Woofer-midrange with magnet protection cover to prevent any damage and undesirable background noise
- Elaborate phase-optimized crossover with 3 settings for the tweeter level
- Designed for installation in suspended ceilings (no housing required) or in closed volumes (20 liters or more)
- 4fold clamping mechanism for very easy and robust installation in surfaces of up to 30 mm thickness
- Removable magnetic metal grill with fine perforations and very slim design for an elegant appearance
- Gold-plated push terminals for cables with cross-sections of up to 6 mm<sup>2</sup>





## HIGH-END IN-CEILING SPEAKER OPTIMIZED FOR USE IN HOME THEATERS

### PRINCIPLE

2-way in-ceiling loudspeaker

### DRIVERS

1 x 6.5" woofer-midrange  
1 x 1" dome tweeter

### POWER HANDLING (RMS/MAX)

110 / 180 watts

### IMPEDANCE

4  $\Omega$

### FREQUENCY RESPONSE

32 - 28000 Hz

### CROSSOVER FREQUENCIES

3100 Hz

### RECOMMENDED AMPLIFIER OUTPUT

20 - 180 watts

### SENSITIVITY

91 dB

### CABINET SURFACE

White

### DIMENSIONS

Outer dimensions:  $\varnothing$  238 mm  
Cutting out:  $\varnothing$  206 mm  
Mounting depth: 130 mm

### WEIGHT

1.82 kg

### ART.NO. /EAN

131 2064 / 40 18843 12064 5

